



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to CECC 22 230, DIN 47297

**Documents**

Assembly instruction 34 A4

**Material and plating**

**Connector parts**

	<b>Material</b>	<b>Plating</b>
Center contact	Brass	AuroDur®, gold plated
Outer contact	Beryllium copper	AuroDur®, gold plated
Body	Brass	Nickel, 2.5-5 µm
Dielectric	PTFE	
Centering sleeve	Brass	Nickel, 2.5-5 µm
Crimping ferrule	Copper	Nickel, 2.5-5 µm

**Electrical data**

Impedance	75 Ω
Frequency	DC to 2 GHz
Return loss	≥ 20 dB, DC to 1 GHz ≥ 18 dB, 1 to 2 GHz
Insertion loss	≤ 0.05 × √f(GHz) dB
Insulation resistance	≥ 2×10 <sup>3</sup> MΩ
Center contact resistance	≤ 4 mΩ
Outer contact resistance	≤ 2.5 mΩ
Test voltage	750 V rms
Working voltage	250 V rms
RF-leakage	≥ 90 dB up to 1 GHz

- Limitations are possible due to the used cable type -

**Mechanical data**

Mating cycles	≥ 500
Center contact captivation	≥ 10 N
Engaging and disengaging force	0.9 N to 10 N
Coupling mechanism retention force	≥ 200 N (screw version, quick-lock)

**Environmental data**

Temperature range	-40°C to +85°C	
Climatic class	IEC 60068-2-1 40/85/21 IEC 60068-2-2 IEC 60068-2-3	
Vibration 2002/95/EC (RoHS)	IEC 60068-2-6 compliant	10 Hz to 2000 Hz, 100m/s <sup>2</sup>

**Tooling**

Crimping tool	11W150-000
Crimp insert	11W150-404

**Suitable cables**

TZC 75025, TZC 75024, BT 3002

**Packing**

Standard	1 pce in bag
Weight	3.6 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Gramsamer J.	09/05/08	S. Mühlbacher	30/03/09	a00	09-s155	S. Peteranderl	26/03/09
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2