



































<p>BNC male terminator gold-pin A : 50 Ω B : 75 Ω C : 93 Ω</p>  	<p>PLU010029 BNC male crimp type gold-pin (RG58U/59U/174U)</p> <p>BNC male crimp type gold-pin (RG58U/59U/174U) teflon insulation</p>  
<p>BNC male chassis mount gold-pin</p>  	<p>BNC female PCB mount gold-pin teflon insulation</p>  
<p>BNC female twist on type gold-pin (RG58U/59U)</p>  	<p>BNC female PCB mount gold-pin</p>  
<p>BNC female bulkhead crimp type gold-pin (RG58U/59U/174U)</p> <p>BNC female bulkhead crimp type gold-pin (RG58U/59U/174U) teflon insulation</p>  	<p>BNC female to F quick connector gold-pin</p>  
<p>Right angle BNC female chassis PCB mount</p>  	<p>BNC female to 3.5mm plug</p>  
<p>Double BNC female bulkhead gold-pin</p>  	<p>BNC female to PAL male</p>  
<p>BNC female bulkhead gold-pin</p>  	<p>BNC male clamp type gold-pin (RG58U/59U)</p> <p>BNC male clamp type gold-pin (RG58U/59U) teflon insulation</p>  
<p>BNC male bulkhead gold-pin</p>  	<p>Right angle BNC male to UHF female gold-pin</p>  
<p>BNC female crimp type gold-pin (RG58U/59U/174U)</p> <p>BNC female crimp type gold-pin (RG58U/59U/174U) teflon insulation</p>  	<p>Right angle BNC male to F female gold-pin</p> 