



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

Compatible to IEC 60169-8, MIL-PRF-39012, CECC 22120

Documents

Panel piercing B 3

Material and plating

Connector parts

	Material	Plating
Center contact	Beryllium copper	Gold, min. 0.8 µm, over nickel
Outer contact	Brass	Nickel, 2.5-5 µm
Body	Brass	Nickel, 2.5-5 µm
Dielectric	PTFE	
Dielectric	POM	

**ADAPTOR
BNC 75 Ω JACK - JACK**

www.pewtronic.cz
PLU010056

Electrical data

Impedance	75 Ω
Frequency	DC to 4 GHz
Return loss	≥ 17 dB, DC to 0.5 GHz
Insertion loss	≤ 0.05 x √ f [GHz] dB, DC to 0.5 GHz
Insulation resistance	≥ 5 x10 ³ MΩ
Center contact resistance	≤ 1.5 mΩ
Outer contact resistance	≤ 1 mΩ
Test voltage	1500 V rms
Working voltage	400 V rms
Power handling (at 20 °C, sea level, VSWR 1.0)	≤ 80 W @ 2 GHz

Mechanical data

Mating cycles	min. 500
Center contact captivation: axial	≥ 15 N

Environmental data

Temperature range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. B
Shock	MIL-STD-202, Meth. 213, Cond. G
Moisture resistance 2002/95/EC (RoHS)	MIL-STD-202, Meth. 106 compliant

Tooling

N/A

Suitable cables

N/A

Packing

Standard	1 pce in bag
Weight	13.9 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	27/07/04	J. Krautenbacher	04/10/06	c00	06-0478	S. Huber-Siegl	04/10/06
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de		Page 2 / 2