



PEWTRONIC s.r.o, Pod Portyčskými skalami 465, 397 01 Písek, Czech Republic,
IČO: 280 72 499, DIČ/VAT: CZ280 72 499, ISO 9001:2008, TÜV SÜD München
Phone:+420 382 217 088, FAX:+420 382 271 361, info@pewtronic.cz, www.pewtronic.cz
Bankovní spojení: UniCredit Bank Czech Republic a.s., číslo účtu: 100223646 /2700
Společnost je zapsána v obchodním rejstříku u Krajského soudu v Č. Budějovicích v oddílu C, vložce číslo 15637

DIN STRAIGHT MALE CONNECTOR FOR 1/4" FLEXIBLE RF CABLE PLU010513

| CONSTRUCTION MATERIALS | |
|-------------------------------|---------------------------|
| INNER CONDUCTOR PIN | BRASS/SILVER PLATING |
| INNER CONDUCTOR SOCKET | TIN BRONZE/SILVER PLATING |
| INSULATOR | PTFE/TPX |
| BODY&OUTER CONDUCTOR | BRASS/TRIMETAL PLATING |
| GASKET | SILICON RUBBER IP67 |

| CODE | PLU010513 | |
|------------------------------------|--|----------|
| DESCRIPTION | DIN STRAIGHT FEMALE CONNECTOR FOR 1/4" FLEXIBLE RF CABLE | |
| CHARACTERISTIC IMPEDANCE | OHM | 50 |
| CUT-OFF FREQUENCY | GHZ | ≤7.5 |
| SHIELDING EFFICIENCY | DB | ≥115 |
| INNER CONDUCTOR CONTACT RESISTANCE | MOHM | ≤0.40 |
| OUTER CONDUCTOR CONTACT RESISTANCE | MOHM | ≤0.20 |
| INSERTION LOSS | DB | ≤0.08 |
| INSULATION RESISTANCE | MOHM | ≥10000 |
| DIELETRIC STRENGHT | V | 3000 |
| VSWR | 0.8-1.0 GHZ | ≤1.08 |
| | 1.7-2.5 GHZ | ≤1.10 |
| WORKING TEMPERATURE RANGE | °C | -65~+165 |
| STORAGE TEMPERATURE RANGE | °C | -65~+165 |