# **Data Sheet**

# Coaxial Cable Connector 11\_SMA-50-3-66/-19\_N

# **Description**

Straight cable plug

Interface standards SUHNER-SMA-26.5GHz



# **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 26.5 \ \text{GHz} \end{array}$ 

**Mechanical Data** 

Outer 2contact soldered Weight 0.0023 kg

**Environmental Data** 

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact		
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Coupling nut	Stainless Steel	
Gasket	VMQ (Silicone rubber)	

## **Related Documents**

Outline drawing DOU-00006516
Catalogue drawing DOU-00006518
Assembly instruction DOC-0000179294

# **Ordering Information**

 Bulk 100 pcs package
 11\_SMA-50-3-66/-19\_NH

 Single package
 11\_SMA-50-3-66/-19\_NE

## **Additional Information**

Suitable cables EZ\_141\_TP\_M17

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only