RADIO FREQUENCY SYSTEMS

The Clear Choice®

N Female Connector for 1/2" RADIAFLEX® cable

These single-piece high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to RADIAFLEX® cables. The connectors provide outstanding value to users because they permit quick, easy and reliable installation at any location, thereby allowing the operator flexibility while saving installation time and money. They attach to prepared cable in one piece assuring error-free attachment. All connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in both type N and 7-16 DIN interface.

FEATURES / BENEFITS


PRODUCT DATASHEET

NF-RA12-012

- Single-piece design for Fast and Easy Installation Reliable and simple attachment avoids unnecessary Θ connector adjustments and provides outstanding performance. Saves time and provides cost savings.
- Robust Mechanical Design Low and consistent IM performance. Θ
- Θ Excellent Electrical Performance - Low VSWR
- Θ Totally Waterproof - Assures safe, long term operation in the harshest of environments.

Technical Features

Image: state of interface N tor Interface N stor Type Straight Method Shrinking S Method Female RICAL SPECIFICATIONS Female RICAL SPECIFICATIONS Ohm 50 Impedance Ohm 50 Method GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	RLK12-50A-Series
ize 1/2" ype Radiating eries all ALF and tor Interface N tor Type Straight Method Shrinking S RICAL SPECIFICATIONS Female Impedance Ohm 50 m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	RLK12-50A-Series
Image: Second	
eries all ALF and tor Interface A N N Straight Method Straight Straight Method Shrinking S Termale RICAL SPECIFICATIONS Ohm 50 GHz 6.0 NICAL SPECIFICATIONS GHz 6.0 NICAL SPECIFICATIONS STRAIGHT STRAIGH	
Image: state of interface N tor Interface N stor Type Straight Method Shrinking S Method Female RICAL SPECIFICATIONS Female RICAL SPECIFICATIONS Ohm 50 Impedance Ohm 50 Method GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
tor Type Straight Method Shrinking S Method Female RICAL SPECIFICATIONS Female RICAL SPECIFICATIONS Ohm 50 Impedance Ohm 50 m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	leeve
Method Shrinking S KICAL SPECIFICATIONS Female RIPedance Ohm 50 m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	leeve
Impedance Ohm 50 m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	leeve
RICAL SPECIFICATIONS Ohm 50 I Impedance Ohm 50 m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
I Impedance Ohm 50 m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
m Frequency GHz 6.0 NICAL SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
Image: Mical SPECIFICATIONS mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
mm (in) 70.8 (2.79) iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
iameter mm (in) 26.8 (1.06) kg (lb) 0.11 (0.24)	
kg (lb) 0.11 (0.24)	
Brase / Dia	
Diass / Fla	ing: Tri metal
Copper / P	ating: Silver
ontact Attachment Spring Fine	er / Plating: silver
ontact Attachment Spring loop	/ Plating: silver
G AND ENVIRONMENTAL	
oof Level IP68	



NF-RA12-012

REV: B

REV DATE: 20. Jul 2015

www.rfsworld.com

Page 1 of 2

All information contained in the present datasheet is subject to confirmation at time of ordering



RADIAFLEX connector



PLU010752 www.pewtronic.com

PRODUCT DATASHEET NF-RA12-012

RADIO FREQUENCY SYSTEMS The Clear Choice[°]



N Female Connector for 1/2" RADIAFLEX® cable

External Document Links	Notes
Application Note	
Installation Instruction	

REV DATE: 20.Jul.2015

Page 2 of 2

All information contained in the present datasheet is subject to confirmation at time of ordering