



Fy^{*1)}xx^{*2)}P7-K120

e.g. FL25P7-K120

*1) y for series FL or FU
 *2) xx No. of contacts 09, 15, 25 or 37

xx	A (mm)	B (mm)	C (mm)
09	30,8	16,9	25
15	39,1	25,2	33,3
25	53	38,9	47,04
37	69,3	55,3	63,5

Technical data for modification (FU)
 Crimp contacts FK20P (AWG 20-24/1,3µm Au) included in delivery.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PEI (-55°C - +130°C)	green
1	1	Insulator front part	PBT	green

Technical data for modification (FL)
 ② Crimp contacts not supplied with connector. Contacts must be ordered separately.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PA66 (-55°C - +115°C)	black
1	1	Insulator front part	PBT	black

Measurement without tolerance acc. to ISO 2768-m SCALE 2:1 DATE 21-11-2003 DRAWN Denzinger CHECKED 13-12-2011 sschref	TITLE D-Sub Crimp Connector		DWG.NO. FyxxP7-K120	REV. 3

COMMENT:
 ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT,
 THIS DRAWING IS NOT TO BE REPRODUCED, COPIED, STORED IN A RETRIEVAL SYSTEM,
 AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.