



Fy*₁)xx*₂)P7-K120

e.g. FL25P7-K120

*1) y for series FL or FU

*2) xx No. of contacts 09, 15, 25 or 37

xx	A (mm)	B (mm)	C (mm)
09	30,8	16,9	25
15	39,1	25,2	33,3
25	53	38,9	47,04
37	69,3	55,3	63,5

Technical data for modification (FU)

Crimp contacts FK20P (AWG 20-24/1,3µm Au) included in delivery.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PEI (-55°C - +130°C)	green
1	1	Insulator front part	PBT	green

Technical data for modification (FL)

② Crimp contacts not supplied with connector. Contacts must be ordered separately.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PA66 (-55°C - +115°C)	black
1	1	Insulator front part	PBT	black

			Measurement without tolerance acc. to ISO 2768-m SCALE 2:1 TITLE D-Sub Crimp Connector				
			DRAWN 21-11-2003 Denzinger				
			CHECKED 13-12-2011 sschref				
3	24-11-2011	23123	www.fctgroup.com	DWG.NO.	FyxxP7-K120	REV.	3
2	17-02-2006	21782					
1							
REV.	DATE	CH.-NO.	ORIGINAL: DIN A3-DRAWING AS A FILE	REPLACEMENT FOR:	FyxxP7-K120 a	PAGES	1