



Fy*1)xx*2)S7-K121

e.g. FL25S7-K121

*1) y for series FL or FU
 *2) xx No. of contacts 09, 15, 25 or 37

xx	A (mm)	B (mm)	C (mm)
09	30,8	16,4	25
15	39,1	24,7	33,3
25	53	38,5	47,04
37	69,3	54,9	63,5

Technical data for modification (FU)
 Crimp contacts FK20S (AWG 20-24/1,3µm Au) included in delivery.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PEI (-55°C - +130°C)	green
1	1	Insulator front part	PBT	green

Technical data for modification (FL)
 ② Crimp contacts not supplied with connector. Contacts must be ordered separately.

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
3	1	Shell	Steel	tin plated
3	1	Insulator rear part	PA66 (-55°C - +115°C)	black
1	1	Insulator front part	PBT	black

		Measurement without tolerance occ. to ISO 2768-m		SCALE	TITLE
				2:1	
		NAME / DATE		D-Sub Crimp Connector	
		DRAWN			
		CHECKED			
				DWG.NO.	FyxxS7-K121
		fctgroup.com		REV.	
2	24-02-2006	21782		REPLACEMENT FOR:	FyxxS7-K121 a
1				ORIGINAL: DIN A3-DRAWING AS A FILE	PAGES 1