

NYLON INSULATED CORD-END TERMINALS (DIN 46228/4)

1. TEMPERATURE RANGE : -40°C UP TO + 105°C
2. TERMINAL MATERIAL : COPPER TUBE
3. PLATING : ELECTRO TIN PLATED
4. INSULATION MATERIAL : NYLON



www.pewtronic.com **PLU020169**

WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)				COLOR SYSTEM			PACKING PCS
		F	L	C	W	FRENCH	GERMAN	DIN	
28 AWG 0.14 mm ²	CE001406	.236 (6.0)	.394 (10.0)	.028 (.70)	.063 (1.6)		GREY		1000 PCS
	CE001408	.315 (8.0)	.472 (12.0)						
26 AWG 0.25 mm ²	CE002506	.236 (6.0)	.394 (10.0)	.030 (.75)	.075 (1.9)	VIOLET	LIGHT BLUE		
	CE002508	.315 (8.0)	.472 (12.0)						
24 AWG 0.34 mm ²	CE003406	.236 (6.0)	.394 (10.0)	.031 (.80)	.075 (1.9)	PINK	TURQUOISE		
	CE003408	.315 (8.0)	.472 (12.0)						
22 AWG 0.5 mm ²	CE005006	.236 (6.0)	.472 (12.0)	.039 (1.0)	.102 (2.6)	WHITE	ORANGE	WHITE	
	CE005008	.315 (8.0)	.551 (14.0)						
	CE005010	.394 (10.0)	.630 (16.0)						
20 AWG 0.75 mm ²	CE007506	.236 (6.0)	.472 (12.0)	.047 (1.2)	.110 (2.8)	BLUE	WHITE	GREY	
	CE007508	.315 (8.0)	.551 (14.0)						
	CE007510	.394 (10.0)	.630 (16.0)						
	CE007512	.472 (12.0)	.709 (18.0)						
18 AWG 1.0 mm ²	CE010006	.236 (6.0)	.472 (12.0)	.055 (1.4)	.118 (3.0)	RED	YELLOW	RED	
	CE010008	.315 (8.0)	.551 (14.0)						
	CE010010	.394 (10.0)	.630 (16.0)						
	CE010012	.472 (12.0)	.709 (18.0)						
16 AWG 1.5 mm ²	CE015008	.315 (8.0)	.551 (14.0)	.067 (1.7)	.138 (3.5)	BLACK	RED	BLACK	
	CE015010	.394 (10.0)	.630 (16.0)						
	CE015012	.472 (12.0)	.709 (18.0)						
	CE015018	.709 (18.0)	.945 (24.0)						
14 AWG 2.5 mm ²	CE025008	.315 (8.0)	.551 (14.0)	.087 (2.2)	.165 (4.2)	GREY	BLUE	BLUE	
	CE025010	.394 (10.0)	.630 (16.0)						
	CE025012	.472 (12.0)	.709 (18.0)						
	CE025018	.709 (18.0)	.945 (24.0)						
12 AWG 4.0 mm ²	CE040010	.394 (10.0)	.669 (17.0)	.110 (2.8)	.189 (4.8)	ORANGE	GREY	GREY	
	CE040012	.472 (12.0)	.787 (20.0)						
	CE040018	.709 (18.0)	1.024 (26.0)						
10 AWG 6.0 mm ²	CE060012	.472 (12.0)	.787 (20.0)	.138 (3.5)	.248 (6.3)	GREEN	BLACK	YELLOW	
	CE060018	.709 (18.0)	1.024 (26.0)						
8 AWG 10 mm ²	CE100012	.472 (12.0)	.866 (22.0)	.177 (4.5)	.299 (7.6)	BROWN	IVORY	RED	
	CE100018	.709 (18.0)	1.102 (28.0)						
6 AWG 16 mm ²	CE160012	.472 (12.0)	.945 (24.0)	.228 (5.8)	.346 (8.8)	IVORY	GREEN	BLUE	
	CE160018	.709 (18.0)	1.102 (28.0)						
4 AWG 25 mm ²	CE250016	.630 (16.0)	1.181 (30.0)	.287 (7.3)	.441 (11.2)	BLACK	BROWN	YELLOW	
	CE250022	.866 (22.0)	1.417 (36.0)						
2 AWG 35 mm ²	CE350016	.630 (16.0)	1.181 (30.0)	.327 (8.3)	.500 (12.7)	RED	BEIGE	RED	
	CE350018	.709 (18.0)	1.260 (32.0)						
	CE350025	.984 (25.0)	1.535 (39.0)						
1/0 AWG 50 mm ²	CE500020	.787 (20.0)	1.417 (36.0)	.406 (10.3)	.591 (15.0)	BLUE	OLIVE	BLUE	
	CE500025	.984 (25.0)	1.575 (40.0)						
2/0 AWG 70 mm ²	CE700021	.827 (21.0)	1.457 (37.0)	.531 (13.5)	.630 (16.0)	YELLOW	YELLOW	YELLOW	100 PCS
3/0 AWG 95 mm ²	CE950025	.984 (25.0)	1.732 (44.0)	.579 (14.7)	.709 (18.0)	RED	RED	RED	
4/0 AWG 120 mm ²	CE120027	1.063 (27.0)	1.890 (48.0)	.657 (16.7)	.787 (20.0)	BLUE	BLUE	BLUE	
250/300 MCM 150 mm ²	CE150032	1.260 (32.0)	2.283 (58.0)	.768 (19.5)	.906 (23.0)	YELLOW	YELLOW	YELLOW	