



**ELECTRICAL CHARACTERISTICS**

Contact Current Rating:3Amperes.  
 Dielectric Withstanding Voltage:AC 500V at sea level.  
 Insulation Resistance:1000Megohms Min.  
 Contact Resistance:30Milliohms Max.  
 Operation Temperature : -55°C to +105°C.

**Material**

Contact :Copper Alloy.  
 Insulator:PBT. [Select PA6T /LCP /PA9T]  
 Shell: SPCC.  
 Screw: Copper Alloy.

Note:

No.	A	B	C	D
09	16.33	24.99	30.81	19.23
15	24.66	33.32	39.14	27.56
25	38.38	47.04	53.04	41.28
37	54.84	63.50	69.32	57.33

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel		TOLERANCE 容許公差	PART NAME 品名 D-SUB SOLDER TYPE STAMPED PIN XXP FEMALE THROUGH HOLE NICKEL SHELL GOLD PLATING ROHS LOW-LEAD
DWG. 製圖 Yumi		SCALE 比例 參考	
DATE 制表日 2007/10/30	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0540-XXFAANXXR
	PAGE 張數 1 OF 1	REV. 版本 A	