

MODULAR PLUG SPECIFICATIONS

ELECTRICAL

CURRENT RATING: 1.5AMP
 VOLTAGE RATING: 12.5VAC
 INSULATION RESISTANCE: 500M Ω Min
 WITH STANDING VOLTAGE: AC1000V RMS 50Hz or 60Hz 1Min
 CONTACT RESISTANCE: 20 Ω MAX

MECHANICAL

CABLE TO PLUG TENSILE STRENGTH: 7.7Kg Min
 DURABILITY: 750MATING CYCLES Min

MATERIAL

HOUSING: POLYCARBONATE(PC)UL 94-0 OR UL 94V-2
 CONTACT: PHOSPHOR BRONZE. HARD PLATED OVER NICKEL SHIELDINJG:
 0.25mm THICKNESS COPPER ALLOY WITH TIN PLATED
 GOLD PLATED: CAT3 - 15 μ m, CAT5E - 50 μ m, CAT6 - 50 μ m
WORKING TEMPERATURE: -40°C ~ 70°C

Modular Plug UTP CAT3 4P4C RJ10 (Strand)
 Modular Plug UTP CAT3 6P4C RJ11 (Strand)
 Modular Plug UTP CAT3 6P6C RJ12 (Strand)



Modular Plug UTP CAT5E 8P8C RJ45 (Solid)



Modular Plug UTP CAT5E 8P8C RJ45 (Strand)



Modular Plug STP CAT5E 8P8C RJ45 (Solid)

PLU020370



Modular Plug STP CAT5E 8P8C RJ45 (Strand)



Modular Plug UTP CAT6 8P8C RJ45 (Solid)



Modular Plug UTP CAT6 8P8C RJ45 (Strand)



Modular Plug STP CAT6 8P8C RJ45 (Solid)



Modular Plug UTP CAT5E 10P10C RJ48 (Strand)