



D-Sub



Thermoplastic top and side entry hoods for spring or slide locking

Identification No. of contacts Part No. Drawing Dimensions in mm

Top entry hood

9-37 way for packaging density of 3 TE (15.24 mm)

No. of contacts	Thermoplastic grey ²⁾	Thermoplastic metallized ³⁾
9	09 67 009 0411	09 67 009 0413
15	09 67 015 0411	09 67 015 0413
25	09 67 025 0411	09 67 025 0413
37	09 67 037 0411	09 67 037 0413
50	09 67 050 0411	09 67 050 0413

	a	b ₁	b ₂	c	d	e	
						min.	max.
9	31.0	23	28	12.8	10	5.75	9.0
15	39.4	28	28	12.8	10	5.75	9.0
25	53.3	34	34	12.8	14	5.75	9.0
37	69.7	43	43	12.8	20	5.75	9.0
50	67.1	41	41	15.8	20	5.75	11.6

Side entry hood

9-37 way for packaging density of 3 TE (15.24 mm)

No. of contacts	Thermoplastic grey ²⁾	Thermoplastic metallized ³⁾
9	09 67 009 0511	09 67 009 0513
15	09 67 015 0511	09 67 015 0513
25	09 67 025 0511	09 67 025 0513
37	09 67 037 0511	09 67 037 0513
50	09 67 050 0511	09 67 050 0513

Top and side entry hood¹⁾

¹⁾ 9-poles is only side entry

No. of contacts	Thermoplastic black ⁴⁾	Thermoplastic metallized ⁴⁾
9	09 67 009 0452	09 67 009 0453
15	09 67 015 0452	09 67 015 0453
25	09 67 025 0452	09 67 025 0453
37	09 67 037 0452	09 67 037 0453
50	09 67 050 0452	09 67 050 0453

	a	c	d	e	
				min.	max.
9	31.0	15.4	7	1.7	7.5
15	39.4	15.4	7	1.7	8.0
25	53.2	15.4	9	1.5	8.0
37	69.5	15.4	9	1.5	8.0
50	67.0	17.9	9	1.5	8.0

D-Sub

²⁾ Operating temperature: -55 °C ... +120 °C
³⁾ Operating temperature: -35 °C ... +60 °C
⁴⁾ Operating temperature: -20 °C ... +90 °C

Accessories see page 05.163