


## LISOVACÍ DUTINKY S IZOLACÍ

GPH

dle DIN 46228

pro Cu laněné vodiče (nelze použít pro plné vodiče!)

**Materiál:**dutinka - měď, galvanicky pocínovaná  
izolace - polyamid nebo polypropylen**Teplotní stálost:** -20°C až +105°C

| Označení  | Průřez<br>vodiče<br>v mm <sup>2</sup> | Barevný<br>kód |    |     | Rozměry<br>v mm |                |                |                |                |                |
|-----------|---------------------------------------|----------------|----|-----|-----------------|----------------|----------------|----------------|----------------|----------------|
|           |                                       | I              | II | III | l <sub>1</sub>  | l <sub>2</sub> | d <sub>1</sub> | d <sub>2</sub> | s <sub>1</sub> | s <sub>2</sub> |
| DI 4-10   | 4                                     | ●              | ●  | ●   | 17,0            | 10,0           | 2,8            | 4,8            | 0,20           | 0,30           |
| DI 4-12   |                                       | ●              | ●  | ●   | 20,0            | 12,0           | 2,8            | 4,8            | 0,20           | 0,30           |
| DI 4-18   |                                       | ●              | ●  | ●   | 26,0            | 18,0           | 2,8            | 4,8            | 0,20           | 0,30           |
| DI 6-12   | 6                                     | ●              | ●  | ●   | 20,0            | 12,0           | 3,5            | 6,3            | 0,20           | 0,30           |
| DI 6-18   |                                       | ●              | ●  | ●   | 26,0            | 18,0           | 3,5            | 6,3            | 0,20           | 0,30           |
| DI 10-12  | 10                                    | ●              | ●  | ●   | 22,0            | 12,0           | 4,5            | 7,6            | 0,20           | 0,40           |
| DI 10-18  |                                       | ●              | ●  | ●   | 28,0            | 18,0           | 4,5            | 7,6            | 0,20           | 0,40           |
| DI 16-12  | 16                                    | ○              | ●  | ●   | 24,0            | 12,0           | 5,8            | 8,8            | 0,20           | 0,40           |
| DI 16-18  |                                       | ○              | ●  | ●   | 28,0            | 18,0           | 5,8            | 8,8            | 0,20           | 0,40           |
| DI 25-16  | 25                                    | ●              | ●  | ●   | 29,0            | 16,0           | 7,3            | 11,2           | 0,20           | 0,40           |
| DI 25-22  |                                       | ●              | ●  | ●   | 36,0            | 22,0           | 7,3            | 11,2           | 0,20           | 0,40           |
| DI 35-16  | 35                                    | ●              | ●  | ●   | 30,0            | 16,0           | 8,3            | 12,7           | 0,20           | 0,40           |
| DI 35-25  |                                       | ●              | ●  | ●   | 39,0            | 25,0           | 8,3            | 12,7           | 0,20           | 0,40           |
| DI 50-20  | 50                                    | ●              | ●  | ●   | 36,0            | 20,0           | 10,3           | 15,0           | 0,30           | 0,50           |
| DI 50-25  |                                       | ●              | ●  | ●   | 40,0            | 25,0           | 10,3           | 15,0           | 0,30           | 0,50           |
| DI 70-20  | 70                                    | ●              | ●  | -   | 37,0            | 20,0           | 12,5           | 16,0           | 0,40           | 0,60           |
| DI 95-25  | 95                                    | ●              | ●  | -   | 44,0            | 25,0           | 14,5           | 18,0           | 0,40           | 0,60           |
| DI 120-27 | 120                                   | ●              | ●  | -   | 48,0            | 27,0           | 16,5           | 21,0           | 0,50           | 0,70           |
| DI 150-32 | 150                                   | ●              | ●  | -   | 58,0            | 32,0           | 19,3           | 23,0           | 0,50           | 1,00           |

**Doplňující údaje:**

- standardní barevný kód pro GPH je II.
- lisovací nářadí viz. kap. 9, 10