

## LISOVACÍ DUTINKY S IZOLACÍ


GPH

pro Cu laněné vodiče (nelze použít pro plné vodiče!)

**Materiál:**

dutinka - měď, galvanicky pocínovaná  
izolace - polyamid nebo polypropylen

**Teplotní stálost:** -20°C až +105°C



Označení	Průřez vodiče v mm <sup>2</sup>	Barevný kód			Rozměry v mm					
		I	II	III	l <sub>1</sub>	l <sub>2</sub>	d <sub>1</sub>	d <sub>2</sub>	s <sub>1</sub>	s <sub>2</sub>
DI 4-10	4	●	●	●	17,0	10,0	2,8	4,8	0,20	0,30
DI 4-12		●	●	●	20,0	12,0	2,8	4,8	0,20	0,30
DI 4-18		●	●	●	26,0	18,0	2,8	4,8	0,20	0,30
DI 6-12	6	●	●	●	20,0	12,0	3,5	6,3	0,20	0,30
DI 6-18		●	●	●	26,0	18,0	3,5	6,3	0,20	0,30
<b>DI 10-12</b>	<b>10</b>	●	●	●	<b>22,0</b>	<b>12,0</b>	<b>4,5</b>	<b>7,6</b>	<b>0,20</b>	<b>0,40</b>
DI 10-18		●	●	●	28,0	18,0	4,5	7,6	0,20	0,40
DI 16-12	16	○	●	●	24,0	12,0	5,8	8,8	0,20	0,40
DI 16-18		○	●	●	28,0	18,0	5,8	8,8	0,20	0,40
DI 25-16	25	●	●	●	29,0	16,0	7,3	11,2	0,20	0,40
DI 25-22		●	●	●	36,0	22,0	7,3	11,2	0,20	0,40
DI 35-16	35	●	●	●	30,0	16,0	8,3	12,7	0,20	0,40
DI 35-25		●	●	●	39,0	25,0	8,3	12,7	0,20	0,40
DI 50-20	50	●	●	●	36,0	20,0	10,3	15,0	0,30	0,50
DI 50-25		●	●	●	40,0	25,0	10,3	15,0	0,30	0,50
DI 70-20	70	●	●	-	37,0	20,0	12,5	16,0	0,40	0,60
DI 95-25	95	●	●	-	44,0	25,0	14,5	18,0	0,40	0,60
DI 120-27	120	●	●	-	48,0	27,0	16,5	21,0	0,50	0,70
DI 150-32	150	●	●	-	58,0	32,0	19,3	23,0	0,50	1,00

**Doplňující údaje:**

- standardní barevný kód pro GPH je II.
- lisovací nářadí viz. kap. 9, 10