


TRONIC (LiYY) flexible, colour coded to DIN 47100, meter marking



B



Technical data

Special PVC data cables, adapted to DIN VDE 0812
 Temperature range flexing -5 °C to +80 °C
 fixed installation -40 °C to +80 °C
 Nominal voltage (not for purposes of high current and power installation)
 0,14 mm² = 350 V
 0,25 mm² = 500 V
 Test voltage up to 0,25 mm² 1200 V
 from 0,34 mm² 2000 V
 Breakdown voltage up to 0,25 mm² 2400 V
 from 0,34 mm² 4000 V
 Insulation resistance min. 20 MΩm x km
 Capacitance (approx.-value) at 800 Hz
 0,14 mm² 120 pF/m
 0,25 mm² 150 pF/m
 Inductance approx. 0,65 mH/km
 Impedance approx. 78 Ωm
 Minimum bending radius flexing 7,5x cable ø
 fixed installation 4x cable ø
 Radiation resistance up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

Bare copper, fine wire conductors, bunch stranded to DIN VDE 0295 cl. 5 and IEC 60228 cl. 5
 Conductor make-up for
 0,14 mm² = 18x0,1 mm
 0,25 mm² = 14x0,15 mm
 0,34 mm² = 7x0,25 mm
 Special PVC core insulation T12, to DIN VDE 0281 part 1
 Colour coded to DIN 47100, but without colour repetition
 Cores stranded in layers with optimal lay-length
 Special PVC outer sheath TM2, to DIN VDE 0281 part 1
 Colour grey (RAL 7001)
 with meter marking, change-over in 2011

Properties

Extremely oil resistant, oil-/ chemical Resistance - see table Technical Informations
 PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
 The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

AWG sizes are approximate equivalent values. The actual cross-section is in mm².
 HELUKABEL®-TRONIC is also available in paired version (e.g. HELUKABEL®-PAAR-TRONIC 20x2x0,14 mm²).
screened analogue type:
 TRONIC-CY (LiY-CY), see page B 9

Application

These cables are used for flexible use with free movement without tensile stress or forced movements in dry, moist and wet rooms but not suitable for open air, wherever the construction requirements call for a minimum outer diameter, TRONIC is the suitable cable to use. This applies especially to such areas as tool making and machine industries as well as electronic, computer, measurement and control sectors.
 CE The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
PLU030011	2 x 0,14	3,3	2,7	13,0	26
	3 x 0,14	3,5	4,0	16,0	26
	4 x 0,14	3,7	5,4	19,0	26
	5 x 0,14	4,0	6,7	22,0	26
	6 x 0,14	4,3	8,1	25,0	26
	7 x 0,14	4,3	9,4	28,0	26
	8 x 0,14	5,1	10,7	35,0	26
	10 x 0,14	5,6	13,4	41,0	26
	12 x 0,14	5,7	16,1	48,0	26
	14 x 0,14	6,0	18,8	53,0	26
	16 x 0,14	6,5	21,5	59,0	26
	18 x 0,14	6,8	24,2	65,0	26
	20 x 0,14	7,1	26,9	70,0	26
	21 x 0,14	7,1	28,2	77,0	26
	24 x 0,14	7,5	32,3	87,0	26
	25 x 0,14	7,7	33,6	91,0	26
	27 x 0,14	7,7	36,3	97,0	26
	30 x 0,14	8,5	40,3	108,0	26
	32 x 0,14	8,8	43,0	114,0	26
	36 x 0,14	9,3	48,4	126,0	26
40 x 0,14	9,6	54,0	139,0	26	
42 x 0,14	9,9	56,0	146,0	26	
44 x 0,14	10,4	59,0	153,0	26	
48 x 0,14	10,5	65,0	164,0	26	
52 x 0,14	11,0	70,0	173,0	26	
56 x 0,14	11,3	75,0	187,0	26	
61 x 0,14	11,6	82,0	204,0	26	
80 x 0,14	13,0	108,0	280,0	26	
100 x 0,14	14,7	135,0	370,0	26	
	2 x 0,25	3,8	4,8	18,0	24
	3 x 0,25	3,9	7,2	22,0	24
	4 x 0,25	4,3	9,6	26,0	24
	5 x 0,25	4,7	12,0	30,0	24
	6 x 0,25	5,3	14,4	36,0	24
	7 x 0,25	5,3	16,8	42,0	24
	8 x 0,25	5,7	19,2	49,0	24
	10 x 0,25	6,6	24,0	57,0	24
	12 x 0,25	6,8	28,8	66,0	24
	14 x 0,25	7,2	33,6	75,0	24
	16 x 0,25	7,6	38,4	84,0	24
	18 x 0,25	8,1	43,2	92,0	24
	19 x 0,25	8,1	46,0	96,0	24
	20 x 0,25	8,6	48,0	101,0	24
	21 x 0,25	8,6	50,0	107,0	24
	24 x 0,25	9,4	60,0	120,0	24
	25 x 0,25	9,5	61,0	132,0	24
	27 x 0,25	9,5	65,0	140,0	24
	30 x 0,25	10,3	72,0	156,0	24
	32 x 0,25	10,9	77,0	164,0	24
36 x 0,25	11,3	86,0	182,0	24	
37 x 0,25	11,3	89,0	190,0	24	
40 x 0,25	11,6	96,0	200,0	24	
42 x 0,25	12,0	101,0	211,0	24	
44 x 0,25	12,6	106,0	225,0	24	
48 x 0,25	12,7	115,0	245,0	24	
52 x 0,25	13,3	125,0	263,0	24	
56 x 0,25	13,9	134,0	280,0	24	
61 x 0,25	14,3	146,0	305,0	24	

Continuation