

3M Round, Shielded Jacketed, Disc. Wire Cable

28 AWG Stranded, Twisted Pair, PVC/PVC

3600X Series



- S Meets external wiring requirements of National Electrical Code, Article 725 (CL2)
- S 28 AWG stranded wire provides flexibility
- S Twisted pairs reduce crosstalk for balanced drive applications
- S Dual shielding with aluminum film foil and copper braid provides excellent EMI/ESD protection
- S Wires are color coded for easy identification
- S 35 db average shielding effectiveness


Date Modified: May 30, 2003

TS-0388-21
Sheet 1 of 2

Physical

Jacket
Material: Polyvinyl Chloride (PVC)
Color: Beige

Primary Material: PVC

Marking
Standard: (UL) CL2 75C 28 AWG 3M XX  AWM II A/B 80C 150V FT1 EU <50V
Where XX maybe MR, NU or NW

Conductors: 28 AWG 7 × 36 [7 × 0.127] Tinned Stranded Copper

Shielding: 001 [0.03] Thick Aluminum Polyester Film Foil and 90% Coverage Tinned Copper Braid.

Electrical

Voltage Rating:	USA: N.E.C. 725, CL2	Canada: 150V	EU: <50V
Insulation Resistance:	(Primary Cable) > 1 × 10 ¹⁰ Ω 10 ft. [3m]		
	Unbalanced	Balanced	
Characteristic Impedance:	58 Ω	91 Ω	
Capacitance:	29.2 pF ft (95.8 pF m)	18.5 pF ft (60.7 pF m)	
Inductance:	.10 μH ft (0.33 μH m)	.15 μH ft (0.49 μH m)	
Propagation Delay:	1.69 ns ft (5.54 ns m)	1.69 ns ft (5.54 ns m)	
Velocity of Propagation:	60%	60%	

Note: Unbalanced is measured between conductors within a pair with one conductor connected to the shield. Balanced is measured between conductors within a pair with the shield floating.

Environmental

Temperature Rating: USA: CL2; 75°C Canada: 80°C

Flammability Rating: USA: N.E.C. 725 CL2 Canada: FT1

UL File No.: E118773, Power Limited Circuit Cable; CL2


3M Round, Shielded Jacketed, Disc. Wire Cable

28 AWG Stranded, Twisted Pair, PVC / PVC

3600X Series



Number of Conductors	Dimension A ± .02
14 (7 pair)	.22 [5.6]
20 (10 pair)	.24 [6.1]
24 (12 pair)	.25 [6.4]
26 (13 pair)	.25 [6.4]
36 (18 pair)	.29 [7.4]
40 (20 pair)	.30 [7.6]
50 (25 pair)	.32 [8.1]
68 (34 pair)	.36 [9.1]
80 (40 pair)	.39 [9.9]
100 (50 pair)	.44 [11.2]



Pair Identification														
Pair	Cond	1st Conductor		Cond	2nd Conductor		Pair	Cond	1st Conductor		Cond	2nd Conductor		
		Solid	Band		Solid	Band			Solid	Band		Solid	Band	
1	1	Black	Red	2	Red	Black	26	51	Brown	Yellow	52	Yellow	Brown	
2	3	Black	White	4	White	Black	27	53	Brown	Orange	54	Orange	Brown	
3	5	Black	Green	6	Green	Black	28	55	Orange	Yellow	56	Yellow	Orange	
4	7	Black	Blue	8	Blue	Black	29	57	Violet	Orange	58	Orange	Violet	
5	9	Black	Yellow	10	Yellow	Black	30	59	Violet	Red	60	Red	Violet	
6	11	Black	Brown	12	Brown	Black	31	61	Violet	White	62	White	Violet	
7	13	Black	Orange	14	Orange	Black	32	63	Violet	Green	64	Green	Violet	
8	15	Red	White	16	White	Red	33	65	Violet	Blue	66	Blue	Violet	
9	17	Red	Green	18	Green	Red	34	67	Violet	Yellow	68	Yellow	Violet	
10	19	Red	Blue	20	Blue	Red	35	69	Violet	Brown	70	Brown	Violet	
11	21	Red	Yellow	22	Yellow	Red	36	71	Violet	Black	72	Black	Violet	
12	23	Red	Brown	24	Brown	Red	37	73	Gray	White	74	White	Gray	
13	25	Red	Orange	26	Orange	Red	38	75	Gray	Brown	76	Brown	Gray	
14	27	Green	White	28	White	Green	39	77	Gray	Red	78	Red	Gray	
15	29	Green	Blue	30	Blue	Green	40	79	Gray	Orange	80	Orange	Gray	
16	31	Green	Yellow	32	Yellow	Green	41	81	Gray	Yellow	82	Yellow	Gray	
17	33	Green	Brown	34	Brown	Green	42	83	Gray	Green	84	Green	Gray	
18	35	Green	Orange	36	Orange	Green	43	85	Gray	Blue	86	Blue	Gray	
19	37	White	Blue	38	Blue	White	44	87	Tan	Orange	88	Orange	Tan	
20	39	White	Yellow	40	Yellow	White	45	89	Tan	Green	90	Green	Tan	
21	41	White	Brown	42	Brown	White	46	91	Tan	Black	92	Black	Tan	
22	43	White	Orange	44	Orange	White	47	93	Tan	Blue	94	Blue	Tan	
23	45	Blue	Yellow	46	Yellow	Blue	48	95	Tan	White	96	White	Tan	
24	47	Blue	Brown	48	Brown	Blue	49	97	Tan	Yellow	98	Yellow	Tan	
25	49	Blue	Orange	50	Orange	Blue	50	99	Tan	Brown	100	Brown	Tan	

Inch
[mm]

Tolerance Unless Noted			
	.0	.00	.000
Inch	± .1	± .05	± .010

[] Dimensions for Reference only

Ordering Information

3600X/XX

Jacket Color Options: _____
 A = "Special" Black Jacket Number of Conductors
 B = "Standard" Beige Jacket (See Table)
 G = "Special" Gray Jacket

Note: Standard length of 14 through 68 conductor cables is 300 ft roll. Standard length of 80 and 100 conductor cables is 200 ft roll.

TS-0388-21
Sheet 2 of 2