

# Product Specifications



**PLU030400** Andrew Virtual Air™ Coaxial Cable, corrugated copper, 1-1/4 in, black PE jacket



## CHARACTERISTICS

### Construction Materials

Jacket Material	PE
Outer Conductor Material	Corrugated copper
Dielectric Material	Foam PE
Flexibility	Standard
Inner Conductor Material	Corrugated copper tube
Jacket Color	Black

### Dimensions

Nominal Size	1-1/4 in
Cable Weight	0.46 lb/ft   0.68 kg/m
Diameter Over Dielectric	34.036 mm   1.340 in
Diameter Over Jacket	39.624 mm   1.560 in
Inner Conductor OD	14.0208 mm   0.5520 in
Outer Conductor OD	36.068 mm   1.420 in

### Electrical Specifications

Cable Impedance	50 ohm $\pm$ 1 ohm
Capacitance	22.0 pF/ft   72.0 pF/m
dc Resistance, Inner Conductor	0.530 ohms/kft   1.740 ohms/km
dc Resistance, Outer Conductor	0.230 ohms/kft   0.750 ohms/km
dc Test Voltage	8500 V
Inductance	0.057 $\mu$ H/ft   0.187 $\mu$ H/m
Insulation Resistance	100000 MOhm
Jacket Spark Test Voltage (rms)	10000 V
Operating Frequency Band	1 – 3700 MHz
Peak Power	180.0 kW

[www.commscope.com/andrew](http://www.commscope.com/andrew)

Join the Evolution

©2010 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. All specifications are subject to change. See [www.commscope.com/andrew](http://www.commscope.com/andrew) for the most current information.

page 1 of 3  
2/24/2010

# Product Specifications

## PLU030400

Pulse Reflection	0.5%
Velocity	92%

## Environmental Specifications

Installation Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)

## General Specifications

Brand	HELIAX <sup>®</sup>
-------	---------------------

## Mechanical Specifications

Bending Moment	29.8 N-m   22.0 ft lb
Flat Plate Crush Strength	75.0 lb/in   1.3 kg/mm
Minimum Bend Radius, Multiple Bends	203.20 mm   8.00 in
Minimum Bend Radius, Single Bend	152.40 mm   6.00 in
Number of Bends, minimum	15
Number of Bends, typical	40
Tensile Strength	154 kg   340 lb

## Standard Conditions

Attenuation, Ambient Temperature	68 °F   20 °C
Average Power, Ambient Temperature	104 °F   40 °C
Average Power, Inner Conductor Temperature	212 °F   100 °C

## Return Loss

Frequency Band	VSWR	Return Loss (dB)
806–960 MHz	1.13	24.30
1700–2170 MHz	1.13	24.30

## Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
0.5	0.056	0.017	117.01
1	0.079	0.024	82.63
1.5	0.097	0.03	67.41
2	0.113	0.034	58.33
10	0.253	0.077	25.89
20	0.36	0.11	18.21
30	0.443	0.135	14.80
50	0.576	0.176	11.39
88	0.772	0.235	8.51
100	0.825	0.251	7.96
108	0.858	0.262	7.65
150	1.019	0.311	6.44

# Product Specifications



## PLU030400

174	1.102	0.336	5.96
200	1.186	0.361	5.53
300	1.471	0.448	4.46
400	1.717	0.523	3.82
450	1.829	0.558	3.59
500	1.937	0.59	3.39
512	1.962	0.598	3.34
600	2.14	0.652	3.07
700	2.329	0.71	2.82
800	2.507	0.764	2.62
824	2.548	0.777	2.58
894	2.666	0.813	2.46
960	2.774	0.846	2.37
1000	2.838	0.865	2.31
1250	3.218	0.981	2.04
1500	3.569	1.088	1.84
1700	3.835	1.169	1.71
1800	3.963	1.208	1.66
2000	4.212	1.284	1.56
2100	4.333	1.321	1.51
2200	4.452	1.357	1.47
2300	4.569	1.393	1.44
2500	4.798	1.463	1.37
2700	5.021	1.53	1.31
3000	5.345	1.629	1.23
3400	5.76	1.755	1.14
3700	6.06	1.847	1.08

## Regulatory Compliance/Certifications

### Agency

RoHS 2002/95/EC

China RoHS SJ/T 11364-2006

### Classification

Compliant

Compliant

