

TE 16X2X0.4 HH2/M

PLU030599

CABLE CONSTRUCTION

CONDUCTOR	BARE COPPER 1 x 0,40																																
INSULATION	SOLID PE O.D. 0.75 ± 0.05 mm																																
PAIR COLOUR IDENTIFICATION	<table> <tr><td>1st</td><td>White + Blue</td></tr> <tr><td>2nd</td><td>White + Orange</td></tr> <tr><td>3rd</td><td>White + Green</td></tr> <tr><td>4th</td><td>White + Brown</td></tr> <tr><td>5th</td><td>Red + Blue</td></tr> <tr><td>6th</td><td>Red + Orange</td></tr> <tr><td>7th</td><td>Red + Green</td></tr> <tr><td>8th</td><td>Red + Brown</td></tr> <tr><td>9th</td><td>Black + Blue</td></tr> <tr><td>10th</td><td>Black + Orange</td></tr> <tr><td>11th</td><td>Black + Green</td></tr> <tr><td>12th</td><td>Black + Brown</td></tr> <tr><td>13th</td><td>Yellow + Blue</td></tr> <tr><td>14th</td><td>Yellow + Orange</td></tr> <tr><td>15th</td><td>Yellow + Green</td></tr> <tr><td>16th</td><td>Yellow + Brown</td></tr> </table>	1 st	White + Blue	2 nd	White + Orange	3 rd	White + Green	4 th	White + Brown	5 th	Red + Blue	6 th	Red + Orange	7 th	Red + Green	8 th	Red + Brown	9 th	Black + Blue	10 th	Black + Orange	11 th	Black + Green	12 th	Black + Brown	13 th	Yellow + Blue	14 th	Yellow + Orange	15 th	Yellow + Green	16 th	Yellow + Brown
1 st	White + Blue																																
2 nd	White + Orange																																
3 rd	White + Green																																
4 th	White + Brown																																
5 th	Red + Blue																																
6 th	Red + Orange																																
7 th	Red + Green																																
8 th	Red + Brown																																
9 th	Black + Blue																																
10 th	Black + Orange																																
11 th	Black + Green																																
12 th	Black + Brown																																
13 th	Yellow + Blue																																
14 th	Yellow + Orange																																
15 th	Yellow + Green																																
16 th	Yellow + Brown																																
MAKE-UP	16 TWISTED PAIRS																																
TAPE	POLYESTER																																
SHIELD	AL/POLYESTER/AL FOIL																																
BRAID	TINNED COPPER BRAID 0,10 mm COV. ≥ 55%																																
RIP CORD	YES																																
JACKET	LSZH GREY RAL7001 O.D. 8.0 mm																																
PRINTING	HAR&CA TE 16x2x0,4HH2/M week/year																																

ELECTRICAL PERFORMANCES

TEMPERATURE RANGE	STATIC: -20°C to + 80°C INSTALLATION: -5°C to + 80°C
-------------------	---

RoHs Compliant

DATA SHEET NO. 114-12
REV. 1.27/08/12