



## Transparent flat cables



**Applications:**  
Transparent flat cable.  
Cable for electronics, loudspeakers, Home Theatre and Hi-Fi Car systems.

**Characteristics:**  
Conductors: n. 1 O.F.C. red copper  
n. 1 O.F.C. tinned copper  
Insulation: Special PVC  
Sheath colour: Transparent

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Nominal section AWG	Elementary wire conductor Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)			
						mt.	Type	Kg.	
C103 TN	2	2 x 0,22	24	0,20	1,8 x 3,7	100	B	1,0	
C105 TN		2 x 0,75	18	0,20	2,4 x 4,8	100	B	2,5	
C203 TN		2 x 1,00	17	0,20	2,8 x 5,6	100	B	3,0	
C237 TN		2 x 1,50	14	0,20	3,0 x 6,0	100	B	4,1	
C238 TN		2 x 2,00	12	0,25	3,5 x 7,0	100	B	5,5	
C100 TN		2 x 3,00	11	0,25	4,1 x 8,2	50	B	8,0	
C134 TN		2 x 4,00	10	0,25	4,1 x 8,2	50	B	4,5	
C135 TN		2 x 6,00	10	0,25	6,1 x 14,0	50	B	8,0	
					17x7x0,20				
					25x7x0,20				



Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
90	49	-15 / +70
32	49	-15 / +70
21	49	-15 / +70
16	49	-15 / +70
14	49	-15 / +70
9	49	-15 / +70
6	49	-15 / +70
5	49	-15 / +70

## Special Extra-flex transparent flat cables



**Applications:**  
Professional Transparent flat cable for loudspeakers, Home Theatre and Hi-Fi Car systems.  
Cable with conductors composed of extremely thin elementary wires (from n° 126 to n° 315 of Ø mm. 0,10) that are first bound up in beams and then stranded for a better transmission of the audio signal.

**Characteristics:**  
Conductors: n. 1 O.F.C. red copper  
n. 1 O.F.C. tinned copper  
Insulation: Special PVC  
Sheath colour: Transparent

tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Nominal section AWG	Cond. Format. mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C191 TS	2	2 x 1,00	17	18x7x0,10	2,8 x 5,6	100	B	3,2
C192 TS		2 x 1,50	16	27x7x0,10	3,0 x 6,0	100	B	4,2
C193 TS		2 x 2,50	13	45x7x0,10	3,8 x 7,7	100	B	6,5
C100 TS		2 x 3,00	12	25x7x0,15	5,8 x 11,2	100	B	12,0



Conductor Resistance Ω/Km ± 5%	Max rated Voltage AC - V	Operative Temperature °C
21	49	-15 / +70
16	49	-15 / +70
12	49	-15 / +70
9	49	-15 / +70