

AWG 24
Shielded
2 to 60
conductors

Flexible shielded black control signal cables
AWG 24 = 0.22 mm² (7 x 0.20, tinned)

UL Style
2464 / 1061

UL Style
2464 / 1061 **Flexible shielded black control signal cables**
AWG 24 = 0.22 mm² (7 x 0.20, tinned)

AWG 24
Shielded
2 to 60
conductors

Summary

Technical data

Copper conductors in AWG sizes, 7-wire, UL 1061 and VDE 0881

No live core conductor

Small conductor and cable diameters

No twist markings

Will not break under vibration

Very flexible

Heat resistant

Cold resistant

Oil resistant to a limited extent

Petrol resistant to a limited extent

Flame-retardant as per UL VW-1/CSA FT-1

Resistant to weathering

Ultraviolet resistant

Suitable for insulation displacement and crimp connectors

Certified:
UL - Style No. 2464
UL - Style No. 1061

Suitable for: connections in and between electrical systems, control systems, regulation systems, measurement systems, signalling systems and pulsed signal systems, especially if the cable must be shielded against external interference, and if the products are intended for export to the USA.

Connection system: low-cost connection using insulation displacement connectors.

Core structure: as per Style No.1061 and VDE 0881, copper strands 7 x 0.20 mm \varnothing tinned = 0.22 mm², insulated with semi-rigid PVC. Insulation wall thickness 0.25 mm, \varnothing of insulated conductor 1.15 mm.

Core labelling: international colour code (see page 228).

Twisted structure: starting with the black conductor, the conductors are twisted clockwise layer by layer from inside out to form the cable core. Ductile fractures are avoided, as the cables do not contain any live central conductors.

Wrapping and shield: The twisted conductors are wrapped in overlapping transparent plastic foil and shielded with a dense braid of tinned copper wires, visual coverage \geq 85%.

Outer jacket: matte black made of special PVC. Colour RAL 9005. No twist markings. The PVC mixture is oil resistant to a limited extent, petrol resistant to a limited extent, flame-retardant, weather resistant and ultraviolet resistant. The wall thickness of the outer jacket increases gradually with the number of conductors from 0.8 mm (2-conductor) to 1.1 mm (60-conductor).

Temperature range:

Heat resistant	105°C as per DIN ISO 6722 (outer jacket)
	80°C (Cores)
Cold resistant	-10°C unrolling and installing
	-30°C storage and operation

Electrical properties:

<u>Operating voltage</u>	300 V
<u>Test voltage</u>	1,500 V
<u>Conductor resistance</u>	(20°C) 87 Ω /km
<u>Insulation resistance</u>	(20°C) \geq 20 M Ω X km
<u>Operating capacitance</u>	One conductor to the remaining conductors, shield earthed approx. 150 pF/metre.


Mechanical properties:

Once-only bending radius	5 X outer diameter
Repeated bending radius	20 X outer diameter

Ordering information

100 m weighs approx.	Overall \varnothing \pm 3%	Number of conductors	Cores	AWG No. Shield Certification	Jacket colour
1.9 kg	4.5 mm	2	2 X	AWG 24 C UL bk	
2.4 kg	4.6 mm	3	3 X	AWG 24 C UL bk	
2.8 kg	4.9 mm	4	4 X	AWG 24 C UL bk	
3.9 kg	5.7 mm	6	6 X	AWG 24 C UL bk	
5.0 kg	6.5 mm	8	8 X	AWG 24 C UL bk	
5.8 kg	6.8 mm	10	10 X	AWG 24 C UL bk	
6.4 kg	7.1 mm	12	12 X	AWG 24 C UL bk	
8.5 kg	7.9 mm	16	16 X	AWG 24 C UL bk	
9.9 kg	8.2 mm	18	18 X	AWG 24 C UL bk	
12.4 kg	9.5 mm	24	24 X	AWG 24 C UL bk	
13.3 kg	9.6 mm	27	27 X	AWG 24 C UL bk	
16.8 kg	10.7 mm	36	36 X	AWG 24 C UL bk	
19.8 kg	11.6 mm	44	44 X	AWG 24 C UL bk*	
22.0 kg	12.0 mm	48	48 X	AWG 24 C UL bk*	

Normal stock unit: 100-m ring. Short sample (20 cm) free of charge.

The rings are marked with the  label. (Cutlength are without Label)
This label is the proof of certification in the USA.



Label



*Items to be sold off



On-time · Fast · Reliable

On-time · Fast · Reliable

