

Technical Document  
 WEB195 50ohm Low Loss Coaxial Cable  
 PE Black

webro

Part Number: 140195F-BLK

Description: WEB195 50ohm Low Loss Coaxial  
 Cable PE Black



**Product Construction**

Conductor Material	:	Plain Annealed Copper
Conductor Stranding	:	Solid, 1/0.94mm
Dielectric Material	:	Foam Polyethylene (FPE)
Dielectric Diameter	:	2.79mm ± 0.15
Screening 1	:	Overall Bonded Aluminium Foil
Screening 1 Coverage	:	> 100%
Screening 2	:	Tinned Copper Wire Braid
Screening 2 Coverage	:	> 90% ± 3
Sheath Material	:	Polyethylene (PE)
Sheath Colour	:	Black



**Mechanical Characteristics**

Overall Diameter	:	4.95mm ± 0.15mm	
Temperature Range	:	Fixed -15°C to +70°C	Flexing -5°C to +70°C
Bend Radius	:	10 x Overall Diameter	
Weight	:	39kg/km	

**Electrical Characteristics**

Inner Conductor DC Resistance	:	≤ 26.0 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 18 Ω /km @ 20°C
Insulation Resistance	:	5000 M Ω.kM
Characteristic Impedance	:	50 Ω ± 3 Ω
Nominal Capacitance	:	83 pF/m
Velocity of Propagation	:	80%
Peak Power	:	2.5 kW
Shielding Effectiveness	:	> 90 dB

**Attenuation @20°C**

Frequency (MHz)	Attenuation (per 100m)	Attenuation (per 100ft)	Power kW	Frequency (MHz)	Attenuation (per 100m)	Attenuation (per 100ft)	Power kW
30	≤ 6.5 dB	≤ 2.0 dB	0.89	1500	≤ 47.7 dB	≤ 14.5 dB	0.12
50	≤ 8.4 dB	≤ 2.5 dB	0.68	1800	≤ 52.5 dB	≤ 16.0 dB	0.11
150	≤ 14.6 dB	≤ 4.4 dB	0.39	2000	≤ 55.4 dB	≤ 16.9 dB	0.10
220	≤ 17.7 dB	≤ 5.4 dB	0.32	2500	≤ 62.4 dB	≤ 19.0 dB	0.09
450	≤ 25.5 dB	≤ 7.8 dB	0.22	5800	≤ 98.1 dB	≤ 29.9 dB	0.06
900	≤ 26.5 dB	≤ 11.1 dB	0.16				

**Certifications & Standards**

RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Fca to BS EN 50575:2014+A1:2016

Publication Date: 16/01/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB

**Webro Cables & Connectors Ltd**

Vision House, Meadow Brooks Business Park, Meadow Lane, Long Eaton, Nottingham NG10 2GD, UK  
 Tel: +44 (0)115 9724483 | Fax: +44 (0)115 9461230 | sales@webro.com | [www.webro.com](http://www.webro.com)

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.