

## 一.特性参数 Specifications

性能/performance	普通型/Common type
抗张强度 MPa(Kg/cm <sup>2</sup> ) Tensile strength	6.9(70)
断裂伸长性% Breaking elongation%	300
撕裂强度 kN/m(kg f/cm) tear strength	14.5(15)
体积电阻率Ω·m(Ω·cm) Volume resistivity	2×10 <sup>12</sup> (2×10 <sup>14</sup> )
介电强度 KV/mm Dielectric strength	25
介电常数 (ε) 50Hz Permittivity	3.2
介质损耗角正切 50Hz Dielectric loss angle tangent	0.001
阻燃性 UL-224 Flame retardancy	-----
使用温度范围℃ Use temperature range C	-50~+200

内径/inside diameter (mm)		厚度 Thickness (mm)	
标准/standard	公差/tolerance	标准/standard	公差/tolerance
Φ1.0	+0.2	0.5	±0.1
	-0.1		
Φ1.5	+0.2	0.5	±0.1
	-0.1		
Φ2.0	+0.2	0.5	±0.1
	-0.1		
Φ2.5	+0.2	0.5	±0.1
	-0.1		
Φ3.0	+0.2	0.5	±0.1
	-0.1		
Φ3.5	+0.2	0.5	±0.1
	-0.1		
Φ4.0	+0.2	0.5	±0.1
	-0.1		
Φ4.5	+0.2	0.5	±0.1
	-0.1		
Φ5.0	+0.2	0.5	±0.1
	-0.1		
Φ6.0	+0.2	0.5	±0.1
	-0.1		
Φ7.0	+0.2	0.5	±0.1
	-0.1		
Φ8.0	+0.2	0.5	±0.1
	-0.1		
Φ9.0	+0.2	0.5	±0.1
	-0.1		
Φ10.0	+0.2	0.5	±0.1
	-0.1		
Φ11.0	+0.2	0.5	±0.1
	-0.1		
Φ12.0	+0.2	0.5	±0.1
	-0.1		
Φ13.0	+0.2	0.5	±0.1
	-0.1		
Φ14.0	+0.2	0.5	±0.1
	-0.1		