


U.I. Lapp GmbH	PRODUCT INFORMATION	
	ÖLFLEX® HEAT 205 SC	12.09.2012

For very high and low temperature requirements
 Small outer diameters for maximum saving of space and weight
 Resistant to contact with mostly all highly aggressive chemical media



Info

Thermal and chemical resistance
 Space and weight-saving
 FEP = fluorinated ethylene propylene

Application range

Conventional cables are not designed for use in environments with very high operating temperatures, heavy usage of chemical agents, or tight spaces
 Typical fields of application - Control cabinets with high heat generation - Measuring instruments - Furnaces and brickworks - Heating equipment and kitchen appliances - Electric motor building - Installations in the chemical industry

Design

Fine-wire, tinned-copper conductor
 FEP core insulation

Product features

ÖLFLEX® HEAT 205 made of FEP - Outstanding resistance against acids, solvents, lacquers, petrol, oils and many other chemical media - Difficult to inflame - High dielectric strength and high abrasion resistance - Low water absorption - Resistant to microbes - Adhesion free insulation materials - Weather and ozone resistant - Hydrophobic and dirt-repellent - High elongation and tear resistance - Resistant against synth. hydraulic fluids

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100kg. Refer to Appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: Coil 100m
 Available as original coil goods only
 Also available on large spools and non-returnable drums.
 Photographs are not to scale and do not represent detailed images of the respective products.
 Article number index of core colours: 000 = green-yellow; 001 = black; 002 = blue; 003 = brown; 005 = yellow; 006 = green; 007 = violet; 008 = pink; 009 = orange; 010 = transparent; 104 = red; 105 = white; 106 = grey
 Other colours are available upon request

Technical Data

Specific insulation resistance:	>2 TΩm x cm
Conductor stranding:	Fine wire according to VDE 0295, class 5/ IEC 60228 class 5 from 0.5 mm ²
Minimum bending radius:	Fixed installation: 4 x outer diameter
Nominal voltage:	U ₀ /U: 300/500 V
Test voltage:	2500 V
Temperature range:	Fixed installation: -100°C to +205°C

Product Management	Document: LAPP_PRO155EN.pdf	1 / 4
--------------------	-----------------------------	-------

Part number	Conductor cross-section (mm²)	Outer diameter (mm)	Core colour	Copper index (kg/km)	Weight (kg/km)
0080001	0.14	1.0	black	1.35	2.6
0080002	0.14	1.0	blue	1.35	2.6
0080005	0.14	1.0	yellow	1.35	2.6
0080006	0.14	1.0	green	1.35	2.6
0080010	0.14	1.0	Transparent	1.35	2.6
0080104	0.14	1.0	red	1.35	2.6
0080105	0.14	1.0	white	1.35	2.6
0081001	0.25	1,15	black	2.4	4
0081002	0.25	1,15	blue	2.4	4
0081003	0.25	1,15	brown	2.4	4
0081005	0.25	1,15	yellow	2.4	4
0081006	0.25	1,15	green	2.4	4
0081009	0.25	1,15	orange	2.4	4
0081010	0.25	1,15	Transparent	2.4	4
0081104	0.25	1,15	red	2.4	4
0081105	0.25	1,15	white	2.4	4
0081106	0.25	1,15	grey	2.4	4
0082000	0.5	1,45	Green/yellow	4.8	6.8
0082001	0.5	1,45	black	4.8	6.8
0082002	0.5	1,45	blue	4.8	6.8
0082003	0.5	1,45	brown	4.8	6.8
0082005	0.5	1,45	yellow	4.8	6.8
0082006	0.5	1,45	green	4.8	6.8
0082007	0.5	1,45	violet	4.8	6.8
0082009	0.5	1,45	orange	4.8	6.8
0082010	0.5	1,45	Transparent	4.8	6.8
0082104	0.5	1,45	red	4.8	6.8
0082105	0.5	1,45	white	4.8	6.8
0082106	0.5	1,45	grey	4.8	6.8
0083000	0.75	1,75	Green/yellow	7.2	10.1
0083001	0.75	1,75	black	7.2	10.1
0083002	0.75	1,75	blue	7.2	10.1
0083003	0.75	1,75	brown	7.2	10.1
0083005	0.75	1,75	yellow	7.2	10.1