

# Hauptkatalog 2014

November 2014

Seite 3

## Kabelschellen SFC48, TFC48 und Kombi



Typ / Spannbereich	Schellenfuß	Bezeichnung	VE [Stk.]
1x Ø 4-8mm	Universal	SFC48	100
2x Ø 4-8mm	Universal	SFC48 2x	100
3x Ø 4-8mm	Universal	SFC48 3x	100
4x Ø 4-8mm	Universal	SFC48 4x	50
<hr/>			
1x, 2x, 3x Ø 4-8mm	C-Profil	TFC48	100
4x, 5x, 6x Ø 4-8mm	C-Profil	TFC48 2x	100
7x, 8x, 9x Ø 4-8mm	C-Profil	TFC48 3x	50
10x, 11x, 12x Ø 4-8mm	C-Profil	TFC48 4x	50
<hr/>			
Kombi 1x, 2x, 3x Ø 4-8mm & 11-29mm	C-Profil	Kombi TFC48 & 11-29	100
Kombi 1x, 2x, 3x Ø 4-8mm & 2x 11-16mm *	C-Profil	Kombi TFC48 & 2x 11-16	100
Kombi 1x, 2x, 3x Ø 4-8mm & 2x 11-29mm	C-Profil	Kombi TFC48 & 2x 11-29	50
PLU990187 Kombi 1x, 2x, 3x Ø 4-8mm & 3x 11-20mm *	C-Profil	Kombi TFC48 & 3x 11-20	50

\* Spannbereich eingeschränkt

Empfohlenes Anzugsmoment: ca. 1-2 Nm, Farbe der Inlays: Schwarz