

# FRAMEWORK TYPE GROUNDING KIT



**PLU990205**

<b>H-GK-1/2F-B</b>	<b>H-GK-1/2SF-B</b>	<b>H-GK-7/8F-B</b>
FOR 1/2" FLEXIBLE RF CABLE	FOR 1/2" SUPER FLEXIBLE RF CABLE	FOR 7/8" FLEXIBLE RF CABLE

**CONSTRUCTION  
MATERIALS AND  
ELECTRICAL  
SPECIFICATION**

<b>GROUNDING WIRE LENGHT</b>	0.8 m
<b>CABLE SECTION ACREAGE</b>	12-30 mm
<b>STRETCHING RESISTANCE</b>	> 500 N
<b>CONTACT MATERIAL</b>	Tinned copper wire braiding
<b>ELECTRIC PRESSURE</b>	> 500 N
<b>INSULATION RESISTANCE</b>	> 500 m Ω
<b>EARTH RESISTANCE</b>	2 m Ω

**TECHNICAL  
CARACTERISTICS**

<b>GROUNDING PART</b>	Tinned copper wire	1
<b>RUBBER GASKET</b>	Rubber	2
<b>GASKET</b>	Stainless steel	2
<b>HEXANGULAR BOLT</b>	Stainless steel	2
<b>COPPER CABLE</b>	Copper	0.8 m
<b>COPPER LUG</b>	Red copper	2
<b>HEXANGULAR BOLT</b>	Stainless steel	1
<b>HEXAGON NUT</b>	Stainless steel	1
<b>SPRING GASKET</b>	Stainless steel	1
<b>SMOOTH GASKET</b>	Stainless steel	1