

Hauptkatalog 2014

November 2014

Seite 3

Kabelschellen SFC48, TFC48 und Kombi



| Typ / Spannbereich | Schellenfuß | Bezeichnung | VE [Stk.] |
|---|-------------|------------------------|-----------|
| 1x Ø 4-8mm | Universal | SFC48 | 100 |
| 2x Ø 4-8mm | Universal | SFC48 2x | 100 |
| 3x Ø 4-8mm | Universal | SFC48 3x | 100 |
| 4x Ø 4-8mm | Universal | SFC48 4x | 50 |
| <hr/> | | | |
| 1x, 2x, 3x Ø 4-8mm | C-Profil | TFC48 | 100 |
| 4x, 5x, 6x Ø 4-8mm | C-Profil | TFC48 2x | 100 |
| 7x, 8x, 9x Ø 4-8mm | C-Profil | TFC48 3x | 50 |
| 10x, 11x, 12x Ø 4-8mm | C-Profil | TFC48 4x | 50 |
| <hr/> | | | |
| Kombi 1x, 2x, 3x Ø 4-8mm & 11-29mm | C-Profil | Kombi TFC48 & 11-29 | 100 |
| Kombi 1x, 2x, 3x Ø 4-8mm & 2x 11-16mm * | C-Profil | Kombi TFC48 & 2x 11-16 | 100 |
| PLU990326 Kombi 1x, 2x, 3x Ø 4-8mm & 2x 11-29mm | C-Profil | Kombi TFC48 & 2x 11-29 | 50 |
| Kombi 1x, 2x, 3x Ø 4-8mm & 3x 11-20mm * | C-Profil | Kombi TFC48 & 3x 11-20 | 50 |

* Spannbereich eingeschränkt

Empfohlenes Anzugsmoment: ca. 1-2 Nm, Farbe der Inlays: Schwarz